

Orange peel grab with 5 tines and 2,000 l or 3,000 l / 6.62c.y. or 3.92c.y. volume for the handling of bulky scrap with excavators from 80t / 176,000lbs to 120t / 264,000lbs operating weight - for heavy duty tasks.

- ▷ With **2 different volumes and 3 shell forms H, W and T.**
- ▷ Hydraulic cylinders are fitted with **replaceable piston rod protection** and are **hydraulically cushioned.**
- ▷ **Oil distribution and hydraulic hoses are protected** in the carrier.
- ▷ **Reinforced tines** made of wear-resistant steel 400HB.
- ▷ **Weld-on tips** made of high resistant forged and tempered steel 500HB.
- ▷ **Accurate fittings** eliminate tine distortion, **solid end stops** (open & close).
- ▷ **Reinforced bolts**, large bearing surface for bolts, specially coated **solid steel bushings.**
- ▷ **Robust, fully integrated rotation** with sturdy slewing ring with internal hoses guarantees optimum force transmission and prevents hose break. The **integrated pressure relief valve** protects against overcharge.
- ▷ **Non-return valve** is optionally available.



Request? scs@kinshofer.com

Orange Peel Grab P120VHD Heavy Duty

Type	Width E (closed) (mm/in)	Opening A (mm/in)	Height C max. (mm/in)	Volume (liter/c.y.)	Number of tines	Weight (kg/lbs)	Load capacity (kg/lbs)
P120VHD-2000-5H	2,280 / 89.8	3,200 / 126.0	3,180 / 125.2	2,000 / 2.62	5	4,570 / 10,054	10,000 / 22,000
P120VHD-2000-5W	2,280 / 89.8	3,200 / 126.0	3,180 / 125.2	2,000 / 2.62	5	4,370 / 9,614	10,000 / 22,000
P120VHD-2000-5T	2,280 / 89.8	3,200 / 126.0	3,180 / 125.2	2,000 / 2.62	5	4,220 / 9,284	10,000 / 22,000
P120VHD-3000-5H	2,390 / 94.1	3,910 / 153.9	3,350 / 131.9	3,000 / 3.92	5	4,700 / 10,340	10,000 / 22,000
P120VHD-3000-5W	2,390 / 94.1	3,910 / 153.9	3,350 / 131.9	3,000 / 3.92	5	4,500 / 9,900	10,000 / 22,000
P120VHD-3000-5T	2,390 / 94.1	3,910 / 153.9	3,350 / 131.9	3,000 / 3.92	5	4,350 / 9,570	10,000 / 22,000

Package consists of: orange peel grab, integrated rotation with sturdy slewing ring, head plate and hose guard

Accessories

Type	Description
KM 501 RD120	upper suspension without pendulum damper adapters for quick change systems from other manufacturers or different sizes on request

Requirements of carrier machine

Operating pressure (open/close):	max. 35 MPa (350 bar) / 5,070 psi
Pump capacity (open/close):	200 - 350 l/min / 53.0 - 92.5 GPM
Operating pressure (rotate):	14 - 25 MPa (140 - 250 bar) / 2,030 - 3,620 psi
Pump capacity (rotate):	20 - 50 l/min / 5.0 - 13.0 GPM

Technical drawings

